

MRV INNENGERÄTE/ Deckenkassette Smart Flow INNENGERÄTE

Modell		AB072MRERA	AB092MRERA	AB122MRERA	AB162MRERA	AB182MRERA	AB242MRERA
Kapazität							
Kühlung	kW	2,20	2,80	3,60	4,50	5,60	7,10
Heizung	kW	2,50	3,20	4,00	5,00	6,30	8,00
Elektrische Parameter							
Stromversorgung	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
Belüftung							
Luftstrom (H/M/L)	m³/h	1000/810/620	1000/810/620	1000/810/620	1000	1000	1380
Schalldruck (H/M/L)	dB(A)	30/27/25	30/27/25	30/27/25	32/29/27	33/30/29	35/34/31
Installation - Abmessungen							
Nettoabmessungen (BxTxH)	mm	840x840x180	840x840x180	840x840x180	840x840x183	840x840x183	840x840x204
Abmessungen der verpackten Einheit (BxTxH)	mm	983x983x268	983x983x268	983x983x268	983x983x268	983x983x268	983x983x290
Netto-/Bruttogewicht	Kg	25,0/28,0	25,0/28,0	25,0/28,0	28/31	28/31	29/32
Ø Flüssigkeitsleitung	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Ø Gasleitung	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	15,88 (5/8)
Paneel							
Modell		PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)
Nettoabmessungen des Paneels (BxTxH)	mm	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50
Verpackungsabmessungen des Paneels (BxTxH)	mm	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123
Netto/Bruttogewicht des Paneels	Kg	6,5/9,0	6,5/9,0	6,5/9,0	6,5/9	6,5/9	6,5/9