

# MRV INNENGERÄTE/Deckenkassette Smart Flow

**INNENGERÄTE**

Modell		AB282MRERA	AB302MRERA	AB382MRERA	AB482MRERA	AB602MRERA
<b>Kapazität</b>						
Kühlung	kW	8,00	9,00	11,20	14,00	16,00
Heizung	kW	9,00	10,00	12,50	16,00	18,00
<b>Elektrische Parameter</b>						
Stromversorgung	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
<b>Belüftung</b>						
Luftstrom (H/M/L)	m³/h	1380/1190/1000	2050/1860/1670	2050/1860/1670	2100/1910/1720	2100/1910/1720
Schalldruck (H/M/L)	dB(A)	37/35/31	37/35/31	37/35/31	44/40/36	44/40/36
<b>Installation - Abmessungen</b>						
Nettoabmessungen (BxTxH)	mm	840x840x204	840x840x246	840x840x246	840x840x288	840x840x288
Abmessungen der verpackten Einheit (BxTxH)	mm	983x983x290	983x983x331	983x983x331	983x983x373	983x983x373
Netto-/Bruttogewicht	Kg	27,0/30,0	31,0/36,0	31,0/36,0	33,0/38,0	33,0/38,0
Ø Flüssigkeitsleitung	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
Ø Gasleitung	mm (Zoll)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)
<b>Paneel</b>						
Modell		PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)
Nettoabmessungen des Paneels (BxTxH)	mm	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50
Verpackungsabmessungen des Paneels (BxTxH)	mm	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123
Netto/Bruttogewicht des Paneels	Kg	6,5/9,0	6,5/9,0	6,5/9,0	6,5/9,0	6,5/9,0