

MRV INNENGERÄT / 2-Wege-Kassette

INNENGERÄT

Modell		AB072MBERA	AB092MBERA	AB122MBERA	AB162MBERA	AB182MBERA
Kapazität						
Kühlung	kW	2,20	2,80	3,60	4,50	5,60
Heizung	kW	2,50	3,20	4,00	5,00	6,30
Elektrische Parameter						
Stromversorgung	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
Belüftung						
Luftstrom (H/M/L)	m³/h	840/700/550	840/700/550	840/700/550	840/700/550	840/700/550
Schalldruck (H/M/L)	dB(A)	42/37/33	42/37/33	42/37/33	44/39/34	44/39/34
Schalleistung (H/M/L)	dB(A)	55/50/46	55/50/46	55/50/46	57/52/47	57/52/47
Installation - Abmessungen						
Nettoabmessungen (BxTxH)	mm	817x620x220	817x620x220	817x620x220	817x620x220	817x620x220
Abmessungen der verpackten Einheit (BxTxH)	mm	1015x695x278	1015x695x278	1015x695x278	1015x695x278	1015x695x278
Netto-/Bruttogewicht	Kg	21,0/23,0	21,0/23,0	21,0/23,0	21,0/23,0	21,0/23,0
Ø Flüssigkeitsleitung	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Ø Gasleitung	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)
Paneel						
Modell		P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB
Nettoabmessungen des Paneels (BxTxH)	mm	1055x680x68	1055x680x68	1055x680x68	1055x680x68	1055x680x68
Verpackungsabmessungen des Paneels (BxTxH)	mm	1110x720x161	1110x720x161	1110x720x161	1110x720x161	1110x720x161
Netto/Bruttogewicht des Paneels	Kg	7,0/8,0	7,0/8,0	7,0/8,0	7,0/8,0	7,0/8,0