

# MRV INNENGERÄT/ Kanaleinbaugerät mit konstantem Volumenstrom

INNENGERÄT

Modell		AD072MQERA	AD092MQERA	AD122MQERA	AD152MQERA	AD182MQERA	AD242MQERA	AD302MQERA
<b>Kapazität</b>								
Kühlung	kW	2,20	2,80	3,60	4,50	5,60	7,10	9,0
Heizung	kW	2,50	3,20	4,00	5,00	6,30	8,00	10,0
<b>Elektrische Parameter</b>								
Stromversorgung	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
<b>Belüftung</b>								
Luftstrom (H/M/L)	m <sup>3</sup> /h	500/410/360	600/510/450	700/580/500	780/680/600	900/780/600	1100/1020/920	1500/1320/1220
Schalldruck (H/M/L)	dB(A)	30/25/23	30/25/23	32/29/26	32/29/26	32/29/26	33/29/25	33/29/25
<b>Installation - Abmessungen</b>								
Nettoabmessungen (BxTxH)	mm	750x635x280	750x635x280	750x635x280	750x635x280	750x635x280	950x635x280	950x635x280
Abmessungen der verpackten Einheit (BxTxH)	mm	980x740x335	980x740x335	980x740x335	980x740x335	980x740x335	1180x740x335	1180x740x335
Netto-/Bruttogewicht	Kg	29,0/35,0	29,0/35,0	29,0/35,0	29,0/35,0	29,0/35,0	34,0/41,0	34,0/41,0
Ø Flüssigkeitsleitung	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)
Ø Gasleitung	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	15,88 (5/8)	15,88 (5/8)
Statischer Druck (Standard/Max.)	Pa	0/200	0/200	0/200	0/200	0/200	50/200	0/200