

# UNITÉ INTÉRIEURE MRV/Cassette 2 voies

UNITE INTERIEURE

Modèle		AB072MBERA	AB092MBERA	AB122MBERA	AB162MBERA	AB182MBERA
<b>Capacité</b>						
Refroidissement	kW	2,20	2,80	3,60	4,50	5,60
Chauffage	kW	2,50	3,20	4,00	5,00	6,30
<b>Paramètres électriques</b>						
Alimentation électrique	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
<b>Ventilation</b>						
Débit d'air (H/M/L)	m <sup>3</sup> /h	840/700/550	840/700/550	840/700/550	840/700/550	840/700/550
Pression acoustique (H/M/L)	dB(A)	42/37/33	42/37/33	42/37/33	44/39/34	44/39/34
Puissance acoustique (H/M/L)	dB(A)	55/50/46	55/50/46	55/50/46	57/52/47	57/52/47
<b>Installation – Dimensions</b>						
Dimensions nettes (LxPxH)	mm	817x620x220	817x620x220	817x620x220	817x620x220	817x620x220
Dimensions unités emballées (LxPxH)	mm	1015x695x278	1015x695x278	1015x695x278	1015x695x278	1015x695x278
Poids net/brut	Kg	21,0/23,0	21,0/23,0	21,0/23,0	21,0/23,0	21,0/23,0
Ø Tuyau liquide	mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Ø Tuyau de gaz	mm (inch)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)
<b>Panneau</b>						
Modèle		P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB	P2B-1055IB
Dimensions nettes de panneau (LxPxH)	mm	1055x680x68	1055x680x68	1055x680x68	1055x680x68	1055x680x68
Dimensions de l'emballage du panneau (LxPxH)	mm	1110x720x161	1110x720x161	1110x720x161	1110x720x161	1110x720x161
Poids net/brut du panneau	Kg	7,0/8,0	7,0/8,0	7,0/8,0	7,0/8,0	7,0/8,0