

# UNITÉ INTÉRIEURE MRV/Cassette 360°

UNITE INTERIEURE

Modèle		AB072MRERA	AB092MRERA	AB122MRERA	AB162MRERA	AB182MRERA	AB242MRERA
<b>Capacité</b>							
Refroidissement	kW	2,20	2,80	3,60	4,50	5,60	7,10
Chauffage	kW	2,50	3,20	4,00	5,00	6,30	8,00
<b>Paramètres électriques</b>							
Alimentation électrique	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
<b>Ventilation</b>							
Débit d'air (H/M/L)	m³/h	1000/810/620	1000/810/620	1000/810/620	1000	1000	1380
Pression acoustique (H/M/L)	dB(A)	30/27/25	30/27/25	30/27/25	32/29/27	33/30/29	35/34/31
<b>Installation – Dimensions</b>							
Dimensions nettes (LxPxH)	mm	840x840x180	840x840x180	840x840x180	840x840x183	840x840x183	840x840x204
Dimensions unités emballées (LxPxH)	mm	983x983x268	983x983x268	983x983x268	983x983x268	983x983x268	983x983x290
Poids net/brut	Kg	25,0/28,0	25,0/28,0	25,0/28,0	28/31	28/31	29/32
Ø Tuyau liquide	mm (pouce)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Ø Tuyau de gaz	mm (pouce)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	15,88 (5/8)
<b>Panneau</b>							
Modèle		PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)	PB-950KB(H)
Dimensions nettes de panneau (LxPxH)	mm	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50
Dimensions de l'emballage du panneau (LxPxH)	mm	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123	1013x1025x123
Poids net/brut du panneau	Kg	6,5/9,0	6,5/9,0	6,5/9,0	6,5/9	6,5/9	6,5/9