

UNITÉ INTÉRIEURE MRV/Cassette 360°

UNITE INTERIEURE

| Modèle | | AB282MRERA | AB302MRERA | AB382MRERA | AB482MRERA | AB602MRERA |
|--|---------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Capacité | | | | | | |
| Refroidissement | kW | 8,00 | 9,00 | 11,20 | 14,00 | 16,00 |
| Chauffage | kW | 9,00 | 10,00 | 12,50 | 16,00 | 18,00 |
| Paramètres électriques | | | | | | |
| Alimentation électrique | Ph-V/Hz | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 |
| Ventilation | | | | | | |
| Débit d'air (H/M/L) | m³/h | 1380/1190/1000 | 2050/1860/1670 | 2050/1860/1670 | 2100/1910/1720 | 2100/1910/1720 |
| Pression acoustique (H/M/L) | dB(A) | 37/35/31 | 37/35/31 | 37/35/31 | 44/40/36 | 44/40/36 |
| Installation – Dimensions | | | | | | |
| Dimensions nettes (LxPxH) | mm | 840x840x204 | 840x840x246 | 840x840x246 | 840x840x288 | 840x840x288 |
| Dimensions unités emballées (LxPxH) | mm | 983x983x290 | 983x983x331 | 983x983x331 | 983x983x373 | 983x983x373 |
| Poids net/brut | Kg | 27,0/30,0 | 31,0/36,0 | 31,0/36,0 | 33,0/38,0 | 33,0/38,0 |
| Ø Tuyau liquide | mm (pouce) | 9,52 (3/8) | 9,52 (3/8) | 9,52 (3/8) | 9,52 (3/8) | 9,52 (3/8) |
| Ø Tuyau de gaz | mm (pouce) | 15,88 (5/8) | 15,88 (5/8) | 15,88 (5/8) | 15,88 (5/8) | 15,88 (5/8) |
| Panneau | | | | | | |
| Modèle | | PB-950KB(H) | PB-950KB(H) | PB-950KB(H) | PB-950KB(H) | PB-950KB(H) |
| Dimensions nettes de panneau (LxPxH) | mm | 950x950x50 | 950x950x50 | 950x950x50 | 950x950x50 | 950x950x50 |
| Dimensions de l'emballage du panneau (LxPxH) | mm | 1013x1025x123 | 1013x1025x123 | 1013x1025x123 | 1013x1025x123 | 1013x1025x123 |
| Poids net/brut du panneau | Kg | 6,5/9,0 | 6,5/9,0 | 6,5/9,0 | 6,5/9,0 | 6,5/9,0 |