

CASSETTE DE 1 VÍA

- 2,5 kW
- 3,5 kW
- 5,0 kW
- 7,1 kW



MODELO			Interior	AB25S2SA1FA(H)	AB35S2SA1FA(H)	AB50S2SA1FA(H)	AB71S2SA1FA(H)
Datos de rendimiento							
Potencia de salida - REFRIGERACIÓN	nom. (min-max)	kW		2,60	3,50	5	6,90
Potencia de salida - CALEFACCIÓN	nom. (min-max)	kW		3,20	4	5,50	7,0
Fuente de alimentación		Fases/V/Hz		1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
Volumen de aire tratado	(H/M/L/Q)	m3/h		500/450/400/350	560/500/450/400	850/700/550/450	900/700/600/500
Unidad interior							
Alta potencia sonora		dB		62	64	65	67
Presión sonora		dB(A)		43/40/37/34	45/42/39/36	47/44/41/38	49/46/43/40
Dimensiones netas	An. x Pr. x Al.	mm		850x540x185	850x540x185	1170x540x185	1170x540x185
Dimensiones del embalaje	An. x Pr. x Al.	mm		1043x648x270	1043x648x270	1363x648x270	1363x648x270
Peso neto/bruto		kg		20,8/24,9	20,8/24,9	26/31	27/32
Datos de instalación							
Tubería de líquido	Ø	mm (pulg.)		6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Tubería de gas	Ø	mm (pulg.)		9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Panel	Modelo			P1B-1028IB	P1B-1028IB	P1B-1348IB	P1B-1348IB
Dimensiones netas del panel (An x P x Al)	An. x Pr. x Al.	mm		1028x600x45	1028x600x45	1348x600x45	1348x600x45
Dimensiones del embalaje del panel (An x P x Al)	An. x Pr. x Al.	mm		1143x688x170	1143x688x170	1463x688x170	1463x688x170
Peso neto/bruto del panel		kg		3,9/8,0	3,9/8,0	5,1/9,8	5,1/9,8