

SUELO-TECHO NUEVO

- 2,5 kW
- 3,5 kW
- 5,0 kW
- 7,1 kW



MODELO			Interior	AC25S2SG2FA(H)	AC35S2SG2FA(H)	AC50S2SG2FA(H)	AC71S2SG2FA(H)
Datos de rendimiento							
Potencia de salida - REFRIGERACIÓN	nom. (min-max)	kW		2,50	3,50	5,00	7,10
Potencia de salida - CALEFACCIÓN	nom. (min-max)	kW		3,10	4,00	5,80	7,80
Fuente de alimentación		Fases/V/Hz		1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
Volumen de aire tratado	(H/M/L/Q)	m3/h		580/480/380/280	750/620/500/400	880/750/650/500	1250/1128/930/840
Unidad interior							
Alta potencia sonora		dB		50	53	57	61
Presión sonora		dB(A)		35/32/28/26	39/36/33/30	44/41/38/35	43/40/38/35
Dimensiones netas	An. x Pr. x Al.	mm		1000x230x680	1000x230x680	1000x230x680	1325x230x680
Dimensiones del embalaje	An. x Pr. x Al.	mm		1100x305x779	1100x305x779	1100x305x779	1425x305x779
Peso neto/bruto		kg		26,0/32,0	26,0/32,0	26,0/32,0	34,0/42,0
Datos de instalación							
Tubería de líquido	Ø	mm (pulg.)		6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Tubería de gas	Ø	mm (pulg.)		9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Controlador							
Estándar				YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01