

FLEXIS PLUS

2,0 kW

2,5 kW

3,5 kW

4,2 kW

5,0 kW

7,1 kW



MODEL	Indoor							
		AS20S2SF1FA-MW3	AS25S2SF1FA-MW3	AS35S2SF1FA-MW3	AS42S2SF1FA-MW3	AS50S2SF1FA-MW3	AS71S2SF1FA-MW3	
		AS20S2SF1FA-MB3	AS25S2SF1FA-MB3	AS35S2SF1FA-MB3	AS42S2SF1FA-MB3	AS50S2SF1FA-MB3	AS71S2SF1FA-MB3	
Performance data								
Output power - COOLING	nom (min-max)	kW	2,00	2,60 (0,80-3,20)	3,50 (1,00-4,00)	4,20 (1,20-4,80)	5,20 (1,40-6,00)	7,00 (2,20-7,50)
Output power - HEATING	nom (min-max)	kW	2,50	3,20 (0,80-4,20)	4,20 (1,00-5,20)	4,40 (1,30-5,80)	6,00 (1,40-6,90)	8,00 (2,40-8,50)
Power Supply		Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Interconnection cable			4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0
Treated air volume	H	m3/h	600	600	650	650	900	1100
Indoor Unit								
High sound power - COOLING		dB	53	53	55	55	57	60
High sound power - HEATING		dB	53	53	55	55	57	60
Sound pressure - COOLING		dB(A)	38/32/25/16	38/32/25/16	39/33/26/17	39/33/26/17	45/41/37/28	47/43/37/33
Sound pressure - HEATING		dB(A)	38/32/25/19	38/32/25/19	39/33/26/20	39/33/26/17	45/41/37/28	47/43/37/33
Net dimensions	WxDxH	mm	856x197x300	856x197x300	856x197x300	856x197x300	999x225x323	1115x235x343
Packaging dimensions	WxDxH	mm	952x283x389	952x283x389	952x283x389	952x283x389	1100x314x420	1202x319x432
Net/gross weight		kg	9,5/12,0	9,5/12,0	9,5/12,0	9,5/12,0	12,0/15,0	15,2/18,2
Installation data								
Liquid pipe	Ø	mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Gas pipe	Ø	mm (inch)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Controller								
Standard			HQ-HJ	HQ-HJ	HQ-HJ	HQ-HJ	HQ-HJ	HQ-HJ