

1-WEGE-KASSETTE

2,5 kW

3,5 kW

5,0 kW

7,1 kW



MODELL	Innen		AB25S2SA1FA(H)	AB35S2SA1FA(H)	AB50S2SA1FA(H)	AB71S2SA1FA(H)
Leistungsdaten						
Ausgangsleistung – KÜHLUNG	nom (min-max)	kW	2,60	3,50	5	6,90
Ausgangsleistung – HEIZUNG	nom (min-max)	kW	3,20	4	5,50	7,0
Stromversorgung		Ph/V/Hz	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
Aufbereitete Luftmenge	(H/M/L/Q)	m3/h	500/450/400/350	560/500/450/400	850/700/550/450	900/700/600/500
Innengerät						
Hohe Schallleistung		dB	62	64	65	67
Schalldruck		dB(A)	43/40/37/34	45/42/39/36	47/44/41/38	49/46/43/40
Netto-Abmessungen	BxTxH	mm	850x540x185	850x540x185	1170x540x185	1170x540x185
Abmessungen der Verpackung	BxTxH	mm	1043x648x270	1043x648x270	1363x648x270	1363x648x270
Netto-/Bruttogewicht		kg	20,8/24,9	20,8/24,9	26/31	27/32
Installationsdaten						
Flüssigkeitsleitung	Ø	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Gasleitung	Ø	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Paneel	Modell		P1B-1028IB	P1B-1028IB	P1B-1348IB	P1B-1348IB
Nettoabmessungen des Paneels	BxTxH	mm	1028x600x45	1028x600x45	1348x600x45	1348x600x45
Verpackungsabmessungen des Paneels	BxTxH	mm	1143x688x170	1143x688x170	1463x688x170	1463x688x170
Netto-/Bruttogewicht des Paneels		kg	3,9/8,0	3,9/8,0	5,1/9,8	5,1/9,8