

# KANALEINBAUGERÄT MITTLERER DRUCK NEU –

3,5 kW

5,0 kW

7,1 kW



MODELL	Innen		AD35S2SM9FA(H)	AD50S2SM9FA(H)	AD71S2SM9FA(H)
<b>Leistungsdaten</b>					
Ausgangsleistung – KÜHLUNG	nom (min-max)	kW	3,50	5,00	7,10
Ausgangsleistung – HEIZUNG	nom (min-max)	kW	4,00	6,00	7,50
Stromversorgung		Ph/V/Hz	1/220~240/50/60	1/220~240/50/60	1/220~240/50/60
Aufbereitete Luftmenge	(H/M/L/Q)	m <sup>3</sup> /h	840/720/600/450	1020/900/780/550	1440/1260/1100/900
Externer statischer Druck		Pa	25(Standard)/37/50/70/90/ 100/110/120/130/150	25(Standard)/37/50/70/90/ 100/110/120/130/150	25(Standard)/37/50/70/90/ 100/110/120/130/150
<b>Innengerät</b>					
Hohe Schalleistung		dB	55	56	58
Schalldruck		dB(A)	41/35/28/26	43/37/30/28	44/41/39/36
Netto-Abmessungen	BxTxH	mm	700x700x248	1100x700x248	1100x700x248
Abmessungen der Verpackung	BxTxH	mm	914x866x318	1316x866x318	1316x866x318
Netto-/Bruttogewicht		kg	26,0/30,0	31,0/35,0	31,0/35,0
<b>Installationsdaten</b>					
Flüssigkeitsleitung	∅	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Gasleitung	∅	mm (Zoll)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)