

Haier

TRUHEN-/ DECKENGERÄT ^{NEU}

2,5 kW

3,5 kW

5,0 kW

7,1 kW



MODELL	Innen		AC25S2SG2FA(H)	AC35S2SG2FA(H)	AC50S2SG2FA(H)	AC71S2SG2FA(H)
Leistungsdaten						
Ausgangsleistung – KÜHLUNG	nom (min-max)	kW	2,50	3,50	5,00	7,10
Ausgangsleistung – HEIZUNG	nom (min-max)	kW	3,10	4,00	5,80	7,80
Stromversorgung		Ph/V/Hz	1/220~240/50/60	1/220~240/50/60	1/220~240/50/60	1/220~240/50/60
Aufbereitete Luftmenge	(H/M/L/Q)	m ³ /h	580/480/380/280	750/620/500/400	880/750/650/500	1250/1128/930/840
Innengerät						
Hohe Schallleistung		dB	50	53	57	61
Schalldruck		dB(A)	35/32/28/26	39/36/33/30	44/41/38/35	43/40/38/35
Netto-Abmessungen	BxTxH	mm	1000x230x680	1000x230x680	1000x230x680	1325x230x680
Abmessungen der Verpackung	BxTxH	mm	1100x305x779	1100x305x779	1100x305x779	1425x305x779
Netto-/Bruttogewicht		kg	26,0/32,0	26,0/32,0	26,0/32,0	34,0/42,0
Installationsdaten						
Flüssigkeitsleitung	Ø	mm (Zoll)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)
Gasleitung	Ø	mm (Zoll)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Steuerung						
Standard			YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01