



Haier

More Creation, More Possibilities

Haier

HVAC Solutions



MULTI

Combine up to 5 indoor units

Haierhvac.eu

Features

Residential MultiSplit Inverter




Introduction

Haier's Multi Split system enables you to experience climate comfort in every room.

A Multi system allows up to 5 indoor units to operate from a single outdoor unit, thereby reducing installation space and costs. All indoor units can be controlled independently and does not need to be installed at the same time, the system can be future proofed to allow up to 5 indoor units to one outdoor unit.

Haier's range of indoor units caters for a wide verity of applications, this includes, wall mounted, concealed ceiling, cassettes and floor standing units. These units are available in range of capacities which enables you to accurately size the system according to the needs of the room.

MultiSplit Unit Connectivity



Outdoor Unit



R32 Refrigerant



High Efficiency



Silence



Easy Installation

Features




SELF-CLEAN

Freezes the evaporator with moisture in the air and removes dirt during the defrost process, ensuring healthy air output. Our Self Clean technology is the first of its kind to integrate the self-cleaning function of both the evaporator and the condenser.



hOn Wi-Fi

Enables you to take control of all the Haier group appliances in your Smart Home from a single app on your smartphone or tablet. The hOn app allows you to manage all the basic functions and much more.



UVC PRO

Inhibits the reproduction of bacteria, by breaking down hydron and oxygen molecule and generates ionic group which inhibits bacteria and sterilises virus after contacting. The module was independently tested by Texcell and inhibits SARS-CoV-2, with an efficiency up to 99.998% in 1 hour (Expert).



EASY INSTALLATION

Installation is simplified, with larger workspaces and easy disassembly and maintenance. Pipes and cables can be connected easily thanks to a removable bottom panel.



SILENCE

Optimised design of fan's air ducts, and motors to be able to deliver cooler, more comfortable air with a low noise level for you to enjoy your indoor space.


















ECO SENSOR

Detects the condition of air and people's movement in real time, adjusting the operating mode of the air conditioner to improve energy efficiency and optimise the users experience. It uses a double area detection with a maximum angle of 120 degrees and a distance of 8m.

Compatibility

Residential MultiSplit Inverter

INDOOR UNITS MULTI-SPLIT R32						
SERIES	2,0 kW	2,5 kW	3,5 kW	5,0 kW	6,8 / 7,1 kW	
SERENE Black & White		 AS25SBBHRA-MW	 AS35SBBHRA-MW	 AS50SDBHRA-MW	 AS71SEPHRA-MW	
		 AS25SBBHRA-MB	 AS35SBBHRA-MB	 AS50SDBHRA-MB	 AS71SEPHRA-MB	
	 Self Clean  56°C Steri Clean  UVC Plus  Coanda Plus  Easy Installation  Silence					
EXPERT Black & White	 AS20XCAHRA	 AS25XCAHRA	 AS35XCAHRA	 AS50XCAHRA	 AS71XCAHRA	
	 AS20XCAHRA-MB	 AS25XCAHRA-MB	 AS35XCAHRA-MB	 AS50XCAHRA-MB	 AS71XCAHRA-MB	
	 Easy Installation  I Feel  Self Clean  Eco Sensor  Easy to disassemble  UVC Pro  2-Way Piping Design					
FLEXIS PLUS Black & White	 AS20S2SF1FA-MB3	 AS25S2SF1FA-MB3	 AS35S2SF1FA-MB3	 AS50S2SF1FA-MB3	 AS71S2SF1FA-MB3	
	 AS20S2SF1FA-MW3	 AS25S2SF1FA-MW3	 AS35S2SF1FA-MW3	 AS50S2SF1FA-MW3	 AS71S2SF1FA-MW3	
	 Easy Installation  I Feel  Silence  Eco Sensor  Easy to disassemble  UVC  Heating Cable (Nordic Ver)					
PEARL PREMIUM	 AS20PBAHRA	 AS25PBHRA - PRE	 AS35PBPHRA - PRE	 AS50PDPHRA - PRE	 AS71PEPHRA - PRE	
	 UVC Pro  I Feel  56°C Steri Clean  Quick Pair					
REVIVE PLUS		 AS25RBAHRA-3	 AS35RBAHRA-4	 AS50RCBHRA-4	 AS68DAHRA-4	
	 Easy Installation  3-Level-Eco  Silence					

INDOOR UNITS MULTI-SPLIT R32						
SERIES	2,5 kW	3,5 kW	4,2 kW	5,0 kW	7,1 kW	
CONSOLE	 AD25S2SD1FA(D)	 AD35S2SD1FA(D)		 AD50S2SD1FA(D)		
	 Silence	 Double Flow	 Compact Design	 Sleep	 56°C Steri Clean	 Heating Cable (Nordic Ver)
CASSETTE 620	 AB25S2SC2FA(H)	 AB35S2SC2FA(H)		 AB50S2SC2FA(H)		
	 28 dBA	 4 Way Independent	 UVC Sterilisation	 Fresh Air	 On-Off Card	
ROUND FLOW CASSETTE					 AB71S2SG1FA(H)	
	 26 dBA	 8 Way Independent	 UVC Sterilisation	 Fresh Air		
CEILING FLOOR	 AC25S2SG1FA(H)	 AC35S2SG1FA(H)		 AC50S2SG1FA(H)	 AC71S2SG1FA(H)	
	 33 dBA	 Flow +	 5 Speed Fan	 Fresh Air	 On-Off Card	 UVC Sterilisation
SLIM DUCT LOW PRESSURE	 AD25S2SS1FA(H)	 AD35S2SS1FA(H)		 AD50S2SS1FA(H)	 AD71S2SS1FA(H)	
	 26 dBA	 Compact Design	 3D	 Condensate Drain Pump	 Flexible Installation	 UVC Sterilisation
DUCTED MEDIUM PRESSURE		 AD35S2SM3FA(H)		 AD50S2SM3FA(H)	 AD71S2SM3FA(H)	
	 26 dBA	 Compact Design	 3D	 Condensate Drain Pump	 Flexible Installation	 UVC Sterilisation
ONE-WAY CASSETTE	 AD25S2SA1FA(H)	 AD35S2SA1FA(H)		 AD50S2SA1FA(H)	 AD71S2SA1FA(H)	
	 Fresh Air	 Compact Design	 UVC Sterilisation			

Outdoor Units

Residential MultiSplit Inverter



1:2 2U40S2SM1FA
2U50S2SM1FA-3



1:3 3U55S2SR5FA
3U70S2SR5FA



1:4 4U75S2SR5FA
4U85S2SR5FA

Outdoor UNIT	Model		2U40S2SM1FA	2U50S2M1FA-3	3U55S2SR5FA	3U70S2SR5FA
Performance data						
Output power - COOLING	nom (min-max)	kW	4,00 (1,10-4,50)	4,60 (1,30-6,00)	5,50 (2,10-7,00)	7,00 (2,40-7,60)
Output power - HEATING	nom (min-max)	kW	4,40 (1,50-4,80)	5,20 (1,60-6,50)	6,80 (1,70-7,60)	7,60 (2,90-8,50)
Absorbed power – COOLING	nom	kW	0,89 (0,30-1,65)	1,07 (0,35-2,01)	1,35	1,84
Absorbed power – HEATING	nom	kW	0,98 (0,38-1,80)	1,21 (0,52-2,00)	1,66	1,85
Energy class	EER	W/W	4,50	4,30	4,00	3,81
	COP	W/W	4,50	4,30	4,10	4,10
COOLING Pdesign	C° 35	kW	4,00	4,60	5,50	7,00
HEATING Pdesign	(C° -10)	kW	3,70	3,80	4,70	6,00
Energy class	SEER		8,50 (A+++)	8,50 (A+++)	8,50 (A+++)	7,50 (A++)
	SCOP		4,60 (A++)	4,60 (A++)	4,00 (A+)	4,20 (A+)
Annual Energy Consumption - COOLING		kWh/a	165	189	227	332
Annual Energy Consumption - HEATING		kWh/a	1126	1157	1678	2012
Outdoor unit						
Power supply		Ph/V/Hz	1/220~240/50/60			
Power cable		N x mm2	3 x 2,5	3 x 2,5	3 x 4,0	3 x 4,0
Interconnection cable		N x mm2	4 x 1,0	4 x 1,0	4 x 2,5	4 x 2,5
Air volume	H	m3/h	2200	2400	3000	3000
Sound power	H	dB	62	63	64	66
Sound pressure	H	(dB(A	56	56	51	53
Running current cooling/heating	Max	A	7,4/8,2	9,0/8,9	10,8/9,5	11,9/9,7
Starting current cooling/heating	Max	A	1,0/1,0	1,0/1,0	4,0/4,0	4,0/4,0
Net dimensions	WxDxH	mm	800x280x550	800x280x550	890x340x700	890x340x700
Packaging dimensions	WxDxH	mm	908x405x625	908x405x625	1010x455x835	1010x455x835
Net/gross weight		kg	34,0/37,0	36,0/39,0	50,0/59,0	54,0/63,0
Compressor type			Twin Rotary Inverter			
Installation data						
Refrigerant			R32	R32	R32	R32
Liquid pipe	Ø	(mm (inch	2×6,35 (3x1/4)	2×6,35 (3x1/4)	3×6,35 (3x1/4)	3×6,35 (3x1/4)
Gas pipe	Ø	(mm (inch	2×9,52 (3x3/8)	2×9,52 (3x3/8)	3×9,52 (3x3/8)	3×9,52 (3x3/8)
Standard pipe length without refrigerant charge		m	20	20	30	30
Maximum pipe length		m	20 (single) 30 (double)	20 (single) 30 (double)	50	60
Maximum IU - OU elevation		m	15	15	15	15
Maximum IU - IU elevation		m	7,5	7,5	7,5	7,5
Refrigerant charge in the factory		kg	1,00	1,10	1,40	1,60
Refrigerant charge in the factory		TCO2eq	0,68	0,74	0,95	1,08
Additional ref, charge over std length		g/m	20	20	20	20
Operating limits - COOLING	min-max	C°	-10-43°C		-10-46°C	
Operating limits - HEATING	min-max	C°	-15-24°C			


4,0 kW	7,0 kW	9,0 kW
5,0 kW	7,5 kW	10,5 kW
5,5 kW	8,5 kW	12,5 kW

Haier



1:5

5U90S2SS5FA
 5U105S2SS5FA
 5U125S2SN1FA



1:3

3S
 3U55S2WR1FA



1:4

3S
 4U70S2WR1FA

4U75S2SR5FA	4U85S2SR5FA	5U90S2SS5FA	5U105S2SS5FA	5U125S2SN1FA
7,50 (2,40-8,70)	8,50 (3,20-9,50)	9,00 (3,20-11,00)	10,00 (3,20-11,00)	12,50 (3,20-13,80)
8,60 (3,10-10,00)	9,60 (4,40-10,50)	10,40 (4,40-11,50)	10,50 (4,40-11,50)	12,70 (4,40-14,30)
1,97	2,50	2,79	3,47	3,87
2,15	2,40	2,79	2,82	3,40
3,80	3,40	3,23	2,88	3,23
4,00	4,00	3,73	3,73	3,73
7,50	8,00	9,00	10,00	12,50
6,30	7,00	7,20	8,00	9,50
7,00 (A++)	7,00 (A++)	7,00 (A++)	7,00 (A++)	7,10 (A++)
4,00 (A+)	4,00 (A+)	4,00 (A+)	4,00 (A+)	4,05 (A+)
379	456	457	537	622
2179	2503	2441	2889	3346
1/220-240/50/60				
3 x 4,0	3 x 4,0	3 x 4,0	3 x 4,0	3 x 4,0
4 x 2,5	4 x 2,5	4 x 2,5	4 x 2,5	4 x 2,5
4000	4000	4200	4200	4200
68	68	70	70	73
55	55	55	55	58
14,7/13,5	15,5/14,6	18,2/14,6	18,2/14,6	23,0/18,7
5,0/5,0	5,0/5,0	5,0/5,0	5,0/5,0	5,0/5,0
890x340x700	890x340x700	920x372x765	920x372x765	950x370x965
1010x455x835	1010x455x835	1045x488x890	1045x488x890	1050x485x1170
61,0/70,0	61,0/70,0	66,0/77,0	66,0/77,0	79,0/91,0
Twin Rotary Inverter				
R32	R32	R32	R32	R32
4×6,35 (4x1/4)	4×6,35 (4x1/4)	5×6,35 (5x1/4)	5×6,35 (5x1/4)	5×6,35 (5x1/4)
3×9,52+1×12,70 (3x3/8+1x1/2)		3×9,52+2×12,70 (3x3/8+2x1/2)		
40	40	40	40	50
70	70	80	80	100
15	15	15	15	15
7,5	7,5	7,5	7,5	7,5
1,60	2,20	2,40	2,40	2,50
1,08	1,49	1,62	1,62	1,69
20	20	20	20	20
-10~46°C				
-15~24°C				


3U55S2WR1FA	4U70S2WR1FA
5,40	7,00
5,00	6,00
1,34	1,80
1,68	2,00
4,05	3,90
4,20	4,30
5,40	7,00
5,00	6,00
8,50 (A+++)	8 (A++)
4,60 (A++)	4,30 (A+)
240	320
1680	1922
1/220-240/50/60	
3 x 4,0	3 x 4,0
4 x 2,5	4 x 2,5
3000	3000
63	63
53	53
12,6/11,5	13/12
4,0/4,0	4,0/4,0
890x340x700	890x340x700
1010x455x875	1010x455x875
55/65	56/66
Twin Rotary (DC inverter)	
R32	R32
3*Ø6,35 (3x1/4)	4*Ø6,35 (4x1/4)
3*Ø9,52 (3x3/8)	4*Ø9,52 (3x3/8)
30	30
50	50
15	15
7,50	7,50
1,80	1,90
1,22	1,28
20	20
-10~46°C	
-15~24°C	

For more details, please refer to the Haier 2025 Catalogue


Technical Illustrations

Residential MultiSplit Inverter


2U40S2SM1FA (2 couplings)




2U50S2SM1FA-3 (2 couplings)




3U55S2SR5FA - 3U70S2SR5FA (3 couplings)




4U75S2SR5FA - 4U85S2SR5FA (4 couplings)






5U90S2SS5FA - 5U105S2SS5FA (5 couplings)



5U125S2SN1FA (5 couplings)



3U55S2WR1FA (3 couplings) + 4U70S2WR1FA (4 couplings)



Haier
HVAC Solutions



Haier HVAC
haierhvac.eu