

FE1W / FE1 - ES50/80/100V



Shock Proof

Ensuring safety for all users



Super Enamel Tank

Ultra-strong durability and anti-corrosion performance.



310S+Mo Heating Element

High anti-corrosion Mo alloy coating, 4 times that of the common heating element.



Bacteria Proof System




Double Tank



Multiposition (V/H)



Butt Welding Technology



Model	ES50V-FE1	ES80V-FE1	ES100V-FE1
Installation type	Vertical + Horizontal	Vertical + Horizontal	Vertical + Horizontal
Control method	Electronic	Electronic	Electronic
Capacity (L)	50	80	100
Material of inner tank	Super enamel tank	Super enamel tank	Super enamel tank
Material of outer body	PCM	PCM	PCM
Material of heating element	310S+Mo	310S+Mo	310S+Mo
Rated voltage (V)/frequency (Hz)	220-240/50	220-240/50	220-240/50
Rated power (W)	2000	2000	2000
Rated temperature (°C)	80	80	80
Rated pressure (bar)	8	8	8
Water-proof grade	IPX4	IPX4	IPX4
Function	WIFI, BPS	WIFI, BPS	WIFI, BPS
Product dimensions W/D/H (mm)	530*323*755	530*323*1068	530*323*1278
Packing dimensions W/D/H (mm)	615*415*860	615*415*1178	615*415*1383
Net weight (kg)	25	34	40
Gross weight (kg)	28	38	44
Energy class	B	B	B
Qty.40HQ	318	212	185