

FE3W / FE3 - ES50/80/100V



Shock Proof

Ensuring safety for all users



DualEnamel™ Heating Tech

Super enamel tank and enamel heating element, corrosion-resistant and high-performance. Consistent heating performance keeping water clean and healthy.



3kW Twin Power

Providing a continuous supply of hot water to meet the high demands of households.



Wi-Fi



ErP Class B



Multiposition (V/H)



Customized Bathing



Bacteria Proof System




AI Anode Anticorrosion System

Lifetime anticorrosion, guaranteed to last without replacement, providing continuous, clean, and healthy hot water.

MAX Indicator
ECO Indicator
BPS Indicator



Control Panel



Model	ES50V-FE3	ES80V-FE3	ES100V-FE3
Installation type	Vertical + Horizontal	Vertical + Horizontal	Vertical + Horizontal
Control method	Electronic	Electronic	Electronic
Capacity (L)	50	80	100
Material of inner tank	Enamel	Enamel	Enamel
Material of outer body	PCM	PCM	PCM
Material of heating element	Enamel	Enamel	Enamel
Rated voltage (V)/frequency (Hz)	220-240/50	220-240/50	220-240/50
Rated power (W)	3000	3000	3000
Rated temperature (°C)	75	75	75
Rated pressure (bar)	8	8	8
Water-proof grade	IPX4	IPX4	IPX4
Function	ECO, BPS, MAX Electronic Anode	ECO, BPS, MAX Electronic Anode	ECO, BPS, MAX Electronic Anode
Product dimensions W/D/H (mm)	530*320*745	530*320*1070	530*320*1312
Packing dimensions W/D/H (mm)	610*410*860	610*410*1178	610*410*1383
Net weight (kg)	25	34	40
Gross weight (kg)	28	38	44
Energy class	B	B	B
Qty.40HQ	318	212	185