

VH3W / VH3 - ES30/50/80/100V

White

Golden

*Available for VH3



Shock Proof

Ensuring safety for all users.



Super Enamel Tank

Ultra-strong durability and anti-corrosion performance.



310S+Mo Heating Element

High anti-corrosion Mo alloy coating, 4 times that of the common heating element.




Ergonomic Control Panel



ErP Class B



U-turn Flow Technology



PUF Technology


310S+Mo Heating Element

U-turn Flow Technology

Magnesium Rod



Smart Wi-Fi Control
*Available for VH3W



Model	ES30V-VH3W/VH3	ES50V-VH3W/VH3	ES80V-VH3W/VH3	ES100V-VH3W/VH3
Installation type	Vertical + Horizontal	Vertical + Horizontal	Vertical + Horizontal	Vertical + Horizontal
Control method	Electronic	Electronic	Electronic	Electronic
Capacity (L)	30	50	80	100
Material of inner tank	Enamel	Enamel	Enamel	Enamel
Material of outer body	SPCC	SPCC	SPCC	SPCC
Material of heating element	310S+Mo	310S+Mo	310S+Mo	310S+Mo
Rated voltage (V)/frequency (Hz)	230/50	230/50	230/50	230/50
Rated power (W)	1500	1500	1500	1500
Rated temperature (°C)	75	75	75	75
Rated pressure (bar)	8	8	8	8
Water-proof grade	IPX4	IPX4	IPX4	IPX4
Function	BPS, ECO (WIFI for VH3W)	BPS, ECO (WIFI for VH3W)	BPS, ECO (WIFI for VH3W)	BPS, ECO (WIFI for VH3W)
Product dimensions W/D/H (mm)	421*410*530	421*410*686	421*410*995	421*410*1230
Packing dimensions W/D/H (mm)	496*486*580	496*486*723	496*486*1032	496*486*1280
Net weight (kg)	13	18	26	30
Gross weight (kg)	15	21	29	34
Energy class	A	B	B	B
Qty.40HQ	384	315	210	192