



AF052MBERA
AF072MBERA
AF092MBERA
AF122MBERA
AF162MBERA
AF182MBERA

*Until stocks last.



Optional controller
HW-BA101ABT



Optional controller
HW-SA201ABK



Optional remote control
YR-HQS01

R410A Units are compatible with R32 wired controllers*

- Double air delivery, upper and lower.
In heating mode: both outputs are enabled, to spread hot air at floor level preventing the "cold feet" effect typical of only higher deliveries.
By acting on the on-board selector it is possible to inhibit the lower output in heating mode.
- **In cooling mode:** The unit works only with the top delivery, the lower output automatically closes.
- Compact and elegant design
- Silent operation
- DC inverter fan motor
- 5 fan speeds selectable with wired controller

Model		AF052MBERA	AF072MBERA	AF092MBERA	AF122MBERA	AF162MBERA	AF182MBERA
Capacity							
Cooling	kW	1,50	2,20	2,80	3,60	4,50	5,00
Heating	kW	1,70	2,60	3,20	4,00	5,00	5,50
Electrical Parameters							
Power supply	Ph/V/Hz	1 / 220-240 / 50					
Ventilation							
Air flow (H/M/L)	m³/h	540/390/270	540/390/270	540/390/270	580/420/270	620/460/270	620/460/270
Sound pressure (H/M/L)	dB(A)	45/38/30	45/38/30	45/38/30	47/40/30	48/42/30	48/42/30
Sound power (H/M/L)	dB(A)	58/52/45	58/52/45	58/52/45	60/54/47	61/55/48	61/55/48
Installation – Dimensions							
Net dimensions (WxDxH)	mm	700x210x600	700x210x600	700x210x600	700x210x600	700x210x600	700x210x600
Packaged unit dimensions (WxDxH)	mm	783x303x695	783x303x695	783x303x695	783x303x695	783x303x695	783x303x695
Net/gross weight	Kg	15,2/18,7	15,2/18,7	15,2/18,7	15,2/18,7	15,2/18,7	15,2/18,7
Ø Liquid pipe	mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Ø Gas pipe	mm (inch)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)	12,70 (1/2)