



AS052MNERAB
AS072MNERAB
AS092MNERAB
AS122MNERAB
AS162MNERA
AS182MNERA
AS242MNERA
AS282MNERA
AS302MNERA

AS**2MNERAC
External EEV

*Until stocks last.



Optional controller
HW-BA101ABT



Optional controller
HW-SA201ABK



Controller
YR-HQS01

R410A Units are compatible with R32 wired controllers*

- Compact, linear design with dimmable information display
- DC inverter fan motor
- External EEV (Optional)
- 5 fan speeds selectable with wired controller



The external EEV modulation valve must be installed in the liquid pipe, between 2m and 5m from the unit. This allows to move this sound source out of the room, reaching high levels of silence for the perfect confort in hotels, commerces or offices.

Model		AS052MNERAB		AS072MNERAB		AS092MNERAB		AS122MNERAB	
		AS052MNERAC		AS072MNERAC		AS092MNERAC		AS122MNERAC	
Capacity									
Cooling		kW	1,50	2,20	2,80	3,60			
Heating		kW	1,70	2,50	3,20	4,00			
Electrical Parameters									
Power supply		Ph/V/Hz	1/220-240/50/60						
Ventilation									
Air flow (H/M/L)		m³/h	500/430/370	550/480/420	600/530/470	630/560/500			
Sound pressure (H/M/L)		dB(A)	33/31/29	35/31/29	36/31/29	37/33/29			
Sound power (H/M/L)		dB(A)	49/46/41	50/47/42	52/48/44	54/51/50			
Installation – Dimensions									
Net dimensions (WxDxH)		mm	855x208x280	855x208x280	855x208x280	855x208x280			
Packaged unit dimensions (WxDxH)		mm	954x279x355	954x279x355	954x279x355	954x279x355			
Net/gross weight		Kg	9,9/12,0	9,9/12,0	9,9/12,0	9,9/12,0			
Ø Liquid pipe		mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)			
Ø Gas pipe		mm (inch)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)			

Model		AS162MNERA	AS182MNERA	AS242MNERA	AS282MNERA	AS302MNERA
		AS162MNERAC	AS182MNERAC	AS242MNERAC	AS282MNERAC	AS302MNERAC
Capacity						
Cooling	kW	4,50	5,60	7,10	8,00	9,00
Heating	kW	5,00	6,30	8,00	9,00	10,00
Electrical Parameters						
Power supply	Ph/V/Hz	1/220-240/50/60				
Ventilation						
Air flow (H/M/L)	m³/h	800/720/650	920/800/720	1010/920/800	1500/1400/1300	1600/1500/1400
Sound pressure (H/M/L)	dB(A)	39/36/34	40/39/35	44/40/36	48/43/40	49/44/41
Sound power (H/M/L)	dB(A)	56/53/51	57/54/52	58/56/54	60/57/53	61/58/54
Installation – Dimensions						
Net dimensions (WxDxH)	mm	1115x243x336	1115x243x336	1115x243x336	1316x270x365	1316x270x365
Packaged unit dimensions (WxDxH)	mm	1206x342x418	1206x342x418	1206x342x418	1403x384x463	1403x384x463
Net/gross weight	Kg	15,8/18,9	15,8/18,9	15,8/18,9	21,8/26,3	21,8/26,3
Ø Liquid pipe	mm (inch)	6,35 (1/4)	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
Ø Gas pipe	mm (inch)	12,70 (1/2)	12,70 (1/2)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)