



AD722MTERAD
AD962MTERAD



Optional controller
HW-BA101ABT



Optional controller
HW-SA201ABK



Optional remote control
YR-HQS01

R410A Units are compatible with R32 wired controllers*

- Flexible and simple ductwork
- Simple maintenance
- Selectable ESP from 100 Pa to 300 Pa by using a wired controller
- Condensate drain pump not included
- 3 speeds + booster

Model		AD722MTERAD	AD962MTERAD
Capacity			
Cooling	kW	22,60	28,00
Heating	kW	25,20	31,50
Electrical Parameters			
Power supply	Ph/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50
Ventilation			
Air flow (H/M/L)	m³/h	4000/3600/3200	4500/3700/3300
Sound pressure level (H/L)	dB(A)	50/46	51/47
Sound power level (H/L)	dB(A)	64/60	65/61
Installation – Dimensions			
Unit Dimensions WxDxH	mm	1438x748x495	1438x748x495
Packaged unit dimensions WxDxH	mm	1558x896x652	1558x896x652
Net weight / Gross weight	Kg	86/102	86/102
Ø Liquid side refrigerant pipe	mm (inch)	12,70 (1/2)	12,70 (1/2)
Ø Gas side refrigerant pipe	mm (inch)	22,22 (7/8)	22,22 (7/8)
Static pressure (Standard / Max)	Pa	100/300	100/300